



LINE · TRANSMISSION & SUBSTATION FITTINGS

80–480 KN

Compression Splice for ACSR Conductor Cable

CFE 2C301-15

Extruded aluminum

Hot-dip galvanized steel

Utilizar herramienta de compresión de 10,000 PSI y cabezal hidráulico, dados de compresión tipo hexagonal. Tolerancia de compresión + 1.5mm

PRODUCT PHOTO




2D DRAWING · DIMENSIONS (MM)

MANGA DE ALUMINIO



ALMA DE ACERO GALVANIZADO



DESCRIPTION

Compression Splice for ACSR Conductor Cable is a product from Partalum's **Transmission & Substation Fittings** line, a Mexican manufacturer of high-voltage electrical connectors and fittings, compliant with the **CFE 2C301-15** standard, made of extruded aluminum. It is available in **4 variants** (PCT-477, PCT-795, PCT-900, PCT-1113).

VARIANTS · SELECTION TABLE BY CONDUCTOR

CATALOG	ACSR CABLE	A	B	ALUMINUM COMPRESSION DIE	STEEL COMPRESSION DIE	FINAL HEX COMPRESSION DIM. — ALUMINUM	FINAL HEX COMPRESSION DIM. — STEEL
PCT-477	477 HAWK	520	140	36	19	32	15.5
PCT-795	795 DRAKE	730	160	50	21	43	17.6
PCT-900	900 CANARY	730	160	50	21	43	17.6
PCT-1113	1113 BLUEJAY	790	190	52	19	44	15.5